




## Flanged Resilient Swing Check Valve (JMH44X2)



### MATERIAL SPECIFICATION

PART NO.	Description	Material Specification	Options
1	Valve Body	Ductile Iron ASTM A536,65-45-12	
2	Bonnet	Ductile Iron ASTM A536,65-45-12	
3	Eye Bolt	Carbon Steel Zinc Plated	
4	O-Ring	NBR ASTM D2000	EPDM ASTM D2000
5	Hinge Pin	Stainless steel 304	
6	Hinge Bushing	Brass ASTM B36 C36000/Hpb63-3	
7	Seat Ring	Bronze ASTM B62 C83600/ZQSn5-5-5(Pressed Fit)	Stainless steel 304/316 , Pressed Fit or Threaded
8	Disc Seat Bolt	Stainless steel 304	
9	Retainer Washer	Bronze ASTM B62 C83600/ZQSn5-5-5	
10	Disc Sealing Ring	EPDM ASTM D2000	Stainless steel 304/316 , Bronze ASTM B62
11	Disc	Ductile Iron ASTM A536,65-45-12	
12	Clapper Arm	Ductile Iron ASTM A536,65-45-12	
13	Stud Bushing	Brass ASTM B16 C36000/Hpb63-3	
14	O-Ring	NBR ASTM D2000	EPDM ASTM D2000
15	Nut	Stainless steel 304	Stainless steel 316

Note:For special material request other than standard specification,please indicate clearly on the inquiry or order list.

Item No.	DN	Dimensions(Inch)					
		L	D	D1	b	N-φL	H
JMH44X2FLG02	2"	7.99	5.98	4.74	0.63	4-0.75	5.24
JMH44X2FLG25	2.5"	10.00	7.01	5.49	0.69	4-0.75	5.91
JMH44X2FLG03	3"	10.94	7.52	6.00	0.75	4-0.75	9.57
JMH44X2FLG04	4"	12.99	9.02	7.50	0.94	8-0.75	11.18
JMH44X2FLG06	6"	15.98	10.98	9.51	1.00	8-0.88	11.42
JMH44X2FLG08	8"	19.49	13.50	11.75	1.12	8-0.88	12.99
JMH44X2FLG10	10"	24.49	15.98	14.25	1.20	12-1.00	13.78
JMH44X2FLG12	12"	25.98	19.02	17.01	1.26	12-1.00	14.80

- Connection Ends: Flange to ASME B16.1 CL 125
- Working Pressure: 300PSI  
200PSI and 250PSI available upon request
- Temperature Range: 0°C- 80°C
- Coating: Fusion Bonded Epoxy Coating in accordance with ANSI/AWWA C550